



VMS Graphics Installation National Certificate of Conformance

VMS Section

Customer: _____ Order Number: _____
Part Number: _____ Kitted By: _____

Installer Section

Installation requirements for Installer

- First review the installation guide for any special installation instructions.
- No visible imperfections (zippers, bubbles, wrinkles) standing 4' from the vehicle
- Removal of vehicle parts is not required
- No plastic, rubber, aluminum, chrome, or silicone surfaces are covered
- At a minimum painted handles are face covered only, visible body paint behind the handle
- Mirrors are or are not covered based on art proof requirements
- Hinges, slider rails, latches, and rails are not covered - visible body paint around / behind
- Visible squeegee strokes in perf are acceptable
- Placement can vary up to 2" from rendering
- Up to 1/8" of visible body paint around trimmed areas (headlights, handles, moldings) is acceptable
- Trim work is clean and unjagged
- Vehicle is post heated 180-200 degrees per material specifications, no lifted edges and no patches
- VMS recommends using Probond Primer if needed
- 3M Primer 94 is to be used ONLY with 3M films
- Relief cuts are to be used only if required per the material specifications
- If any removable badges interfere with the graphics. they must be removed and placed in the glove box . DO NOT DISCARD.

The intention is a cleanly installed, legibly read, advertisement that lasts years with proper care.

VIN Number: _____
Installer _____ Date: _____
Comments: _____

Instructions

1. Send in install pictures to VMS
2. Have customer sign of on install below
3. Return form by email to installations@vmsinc.com

Customer Section

By signing this form the customer agrees that the work performed was completed and acceptable.

Signature: _____ Date: _____
Comments: _____